

RECO USA Standard

Hot Water Storage Tanks & Storage Water Heaters

Model Example Storage Tank STV150-48084US
 Storage Tank Vertical, 150 PSI, 48" OD x 84" Ultra-Stone Lined

Model Example Storage Water Heater SHH150-54120US-10096-DS
 Storage Heater Horizontal, 150 PSI, 54" OD x 120" Ultra-Stone Lined, 10 x 96 coil, Double Wall, Steam

OD	OAL	Gallons		Fitting Group	OD	OAL	Gallons		Fitting Group
		Nom	Act				Nom	Act	
18	48	50		1	60	96	1130		4
18	60	80		1	60	120	1420		4
24	48	95		2	60	144	1720		4
24	60	120		2	60	168	2000		4
24	72	140		2	60	192	2300		4
24	84	165		2	60	216	2600		4
30	48	147		2	60	240	2900		4
30	60	185		2	66	120	1700		5
30	75	220		2	66	144	2050		5
30	84	255		2	66	168	2400		5
30	96	290		2	66	192	2800		5
30	108	330		2	66	216	3200		5
30	120	360		2	72	96	1700		5
36	72	310		3	72	120	2100		5
36	84	365		3	72	144	2500		5
36	96	420		3	72	168	2900		5
36	108	475		3	72	192	3300		5
36	120	525		3	72	216	3700		5
36	144	640		3	72	240	4100		5
42	72	430		3	72	288	5000		5
42	84	500		3	84	120	2880		6
42	96	575		3	84	144	3460		6
42	108	650		3	84	168	4030		6
42	120	720		3	84	192	4600		6
42	132	790		3	84	216	5180		6
42	144	860		3	84	240	5760		6
42	156	930		3	84	264	6330		6
42	168	1000		3	84	288	6900		6
48	72	560		4	96	120	4500		7
48	84	655		4	96	144	4500		7
48	96	750		4	96	168	5260		7
48	108	845		4	96	192	6010		7
48	120	950		4	96	216	6760		7
48	132	1045		4	96	240	7520		7
48	144	1140		4	96	264	8270		7
48	156	1225		4	96	288	9020		7
48	168	1310		4	96	312	9770		7
48	192	1500		4	96	336	10530		7
54	96	950		4	96	360	11280		7
54	120	1190		4					
54	144	1430		4					
54	168	1670		4					
54	192	1900		4					
54	216	2130		4					

Standard Fitting Group Sizes

Group	Inlet/Outlet	Recirculating	Drain	Relief Valve
1	1	1	3/4	1
2	1 ½	1 ½	1	1
3	1 ½	1 ½	1 ½	1 ½
4	2	2	2	1 ½
5	2 ½	2 ½	2 ½	1 ½
6	3	3	2 ½	1 ½
7	4 FLG	4 FLG	2 ½	1 ½